18000 series

Snap-action momentary pushbutton switches

Distinctive features and specifications





- ❑ **Panel and PC mount models**
- ❑ **Snap-in panel mounting version**
- ❑ **Tactile feedback**

B

ELECTRICAL SPECIFICATIONS

- Max. current/voltage rating with resistive load :
  - gold plated brass contacts : 100mA - 30VDC
  - gold plated silver contacts : 1A 125VAC, 1A 30VDC
- Initial contact resistance : 50 mΩ max.
- Insulation resistance : 1.000 MΩ min.
- Dielectric strength : 1.000 Vrms 50 Hz min.
- Electrical life : 60.000 cycles at full load

Models for high currents : see 18635A and 18645A at the end of the series.

MATERIALS

- Case : PBT
- Actuator : polyamide, glass filled
- Bushing : brass, nickel plated
- Housing : stainless steel
- Bracket : tin plated steel
- Contacts
  AD : silver, gold plated
  CD : brass, gold plated
- Terminal seal : epoxy

GENERAL SPECIFICATIONS


- Total travel : 0,5 mm (.019)
- Torque : 1,25 Nm (.922 Ft.lb) max. applied to nut
- Operating temperature : -30°C to +65°C
- Soldering : 300°C, 3 sec. max.

18000 series

Snap-action momentary pushbutton switches

MODEL STRUCTURE

Overview



SERIES

Number of poles

3	Single pole
4	Double pole

Terminals

Blank	Solder lugs or straight PC depending on model
W	Right angle, horizontal mounting
WW	Right angle, vertical mounting
Y	Bracket mounting

Terminals and bushing

2	Straight PC terminals with Ø 6,35 (1/4) threaded bushing Straight PC terminals + bracket or right angle terminals with plain bushing
5	Solder lug terminals with Ø 6,35 (1/4) threaded bushing.
7	Solder lug terminals with Ø 6,35 (1/4) flatted bushing.
8	Solder lug terminals, snap-in mounting
9	Straight PC terminals with Ø 6,35 (1/4) flatted bushing.

Electrical function

5	ON	-	MOM

ABOUT THIS SERIES

On the following pages, you will find successively :
- model structure of switches
- options in the same order as in above chart

Dimensions : first dimensions are in mm while inches are shown as bracketted numbers.

NOTICE : please note that not all combinations of above numbers are available. Refer to the following pages for further information.

OPTIONS

18000 series

Snap-action momentary pushbutton switches

Overview

Contact materials

AD Silver, gold plated
CD Brass, gold plated

Special options

X624 Shorter bushing and plunger
X662 Snap-in mounting and straight PC terminals

Other : specific bushings, etc... See following pages.

Bezels

For snap-in mounting models
U1200
U1210 for LED
For bracket mounting models
U3200

Plungers

-13 Ø 4 (.157), length 6 mm (.236)
Standard with threaded bushing
-6 Ø 3,1 (.122), length 5,85 mm (.230)
-3 Ø 4 (.157), length 5,5 mm (.216)
Standard with plain bushing
-5 Ø 3,1 (.122), length 6,3 mm (.248)

Caps

For Ø 4 (.157) plungers (-3, -13)
U900 Ø 5 (.196)
U1140 Ø 8 (.314)
U1720 Ø 9,4 (.370)
U480 Ø 10 (.393) - standard
U630 Ø 15 (.590)
U2430 Square
Height 4 (.157)
U2020 Square
Height 6 (.236)

For Ø 3,1 (.122) plungers (-5, -6)
U2400 Ø 5 (.196)
U2510 Ø 8 (.314)
U2130 Ø 9,4 (.370)
U2900 Ø 10 (.393)
U3400 Ø 15 (.590)
U910 Square
Height 4 (.157)
U2340 Square
Height 6 (.236)

Sealing boots are available to protect the switches against dust and water. They are presented in section H.

Mounting accessories : standard hardware supplied with all models with Ø 6,35 (1/4) threaded bushing : 2 hex nuts 8 mm (.314) across flats, 1 locking ring and 1 lockwasher.
Standard and special hardware available are presented in section I.


Packaging unit : 25 pieces for W, WW double pole and 18800 models
50 pieces for other models.

18000 series


Snap-action momentary pushbutton switches

Threaded bushing Ø 6,35 (1/4) : 18500 - 18700 - 18200


MODEL STRUCTURE



- Solder lug or straight PC terminals
- Epoxy sealed terminals standard



MODEL STRUCTURE




Shown with standard plunger (-13)

B

Solder lug terminals : 18500




	1-3	1-2
Single pole **18535**	ON	MOM
Double pole **18545**	ON	MOM



Flatted bushing - solder lug terminals : 18700




	1-3	1-2
Single pole **18735**	ON	MOM
Double pole **18745**	ON	MOM



Straight PC terminals : 18200



	1-3	1-2
Single pole **18235**	ON	MOM
Double pole **18245**	ON	MOM



MODEL STRUCTURE

18000 series


Snap-action momentary pushbutton switches

Threaded bushing Ø 6,35 (1/4) : 18900 - Snap-in mounting : 18800

Flatted bushing - straight PC terminals : 18900



	1-3	1-2
Single pole **18935**	ON	MOM
Double pole **18945**	ON	MOM



B


Snap-in mounting - solder lug terminals : 18800

Shown with cap U910 + U1200




	1-3	1-2
Single pole **18835**	ON	MOM
Double pole **18845**	ON	MOM

Available with straight PC terminals : see X662 under "Special options".




PANEL CUT-OUT

18500 - 18200




18700 - 18900




PANEL CUT-OUT

18800



With bezel **U1200**




With bezel **U1210** for LED

18000 series


Snap-action momentary pushbutton switches

Plain bushing : 18200Y - 18200W - 18200WW


MODEL STRUCTURE



- Straight PC or right angle terminals
- Epoxy sealed terminals standard



MODEL STRUCTURE



Shown with standard plunger (-3)


B

Straight PC terminals - bracket mounting - single pole 18230Y



18235Y

ON MOM




Straight PC terminals - bracket mounting - doube pole 18240Y



18245Y

ON MOM



Right angle terminals - horizontal : 18200W




Single pole
18235W

ON MOM

Double pole
18245W

ON MOM




Right angle terminals - vertical : 18200WW





	1-3	1-2
Single pole **18235WW**	ON	MOM
Double pole **18245WW**	ON	MOM



B

CONTACT MATERIALS




AD Silver, gold plated
CD Brass, gold plated

PLUNGERS




Dash compulsory before plunger code.



-13


Ø 4 (.157) - standard with threaded bushing



-6


Ø 3,1 (.122)

If plunger not specified, we supply former default option -13.



-3

Ø 4 (.157) - standard with plain bushing



-5

Ø 3,1 (.122)

18000 series

Snap-action momentary pushbutton switches

OPTIONS

SPECIAL OPTIONS




F Tin dipped terminals (for PC terminals only)

X624 Straight PC terminals - bracket mounting - **with shorter bushing and plunger**




Single pole

18235Y -2X624 ON MOM



Double pole

18245Y -2X624 ON MOM




X662 **Snap-in mounting - straight PC terminals**



Single pole
18835 X662 ON MOM

Double pole
18845 X662 ON MOM



SPECIAL OPTIONS (continued)




X371 Plain bushing Ø 6,25 mm (.246) (instead of standard threaded bushing).


X372 Shorter threaded bushing Ø 6,35 (1/4). **Height 7 mm (.274).**

X386 Threaded bushing Ø 6,35 mm (1/4) to replace plain bushing on models W - WW and Y.


X438 Plain bushing Ø 6,25 mm (.246). **Height 7,2 mm (.283)** - **without shoulder.**




X372



X371



X438




X386

B


CAPS




Caps for Ø 4 (.157) plungers (-13, -3)




U900




U1140




U1720




U480



U630



U2430
Square




U2020
Square

Cap colours			
Replace last "0" by number			
1	blue	**5**	yellow
1/4	dark blue	**6**	red
2	black	**7**	ivory
3	green	**7/1**	white
4	grey	**9**	orange


CAPS (continued)




Caps for Ø 3,1 (.122) plungers (-5, -6)




U2400




U2510




U2130




U2900



U3400



U910
Square




U2340
Square

Cap colours


Replace "0" by number

1	blue
1/4	dark blue
2	black
3	green
4	grey
5	yellow
6	red
7	ivory
7/1	white
9	orange

Caps for 18800 and 18800X662 models



U910
Square




U2340
Square

DRESS NUTS


For models with threaded bushing (18500 - 18700 - 18200 - 18900)

Chrome plated - Order separately.




U1636

For caps U1140 and U2510



U840

For cap U480 and U2900




U825

For caps U630 and U3400


BEZELS



For snap-in models (18800 - 18800X662)



U1200




U1210

For LED Ø 5 - not supplied

Bezel colours	
Replace last "0" by number	
1	blue
1/4	dark blue
2	black
3	green
4	grey
5	yellow
6	red
7	ivory
7/1	white
9	orange


For bracket mounting models (18200Y & 18200YX624)




U3200

STANDARD PANEL MOUNTING

Panel thickness with bezel : 1 mm (.039) to 2,5 mm (.098)



18800 + U910 + U1200



18800 + U910 + U1210