Przełączniki przyciskane R13 HOWO

Model's instruction

R13 — 508/ □ □ □ □ □ □

- Means indicative light voltage
- B means with filament lamp, L means shining diode, N means with neon lamp
- Means push button cover color:R.G.Y means red, green and yellow.
- 1 means self-lock(alternately), 2 means no lock(instantaneously), 0 means no machinery movement.
- Circuit component: 1 means one way 2 means circuit component
- Category sequence:means installation whorl
- Outer shell form:508 means square
- Main type code:R13 means push button swich with lamp, (F) means push button switch without lamp

Specifications

Ambient temperature	Relative humidity	Rated Voltage	Rated current	Contact resistance	Insulation resistance	Test voltage	Actuating force	Life
-55~+85°C	98%、+40°C	250VAC	1.5A	≤ 0.05 Ω	≥ 1000M Ω	1500VAC	1~4N	100000


Capacity lighting unit



Voltage(V)	Item	Current mA
2	L	20
	B	/
	N	/
6	L	20
	B	70
	N	/
12	L	20
	B	37
	N	/
24	L	20
	B	24
	N	/

demensions

square



Panel cut-out




Circuit chart



R13-508/2

Normally colse(Instantaneously)



R13-508/1

Alternative(alternately)