
Support Post (Metric)

Spacer Bolts DIA

[Polyamide, metric thread]





Spacer bolts

Type	hexagonal
Styles	internal / external
Material	Polyamide 6.6 / DMS 824
Colour	black
Standard Pack	from 100 pcs

Internal thread lengths [mm]

L (mm)	L2 (mm)
5	3,0
from 6	4,0
from 8	6,0
from 10	8,0
from 12	10,0

External thread lengths [mm]

G1=G2	L3 (mm)
M2,5	8
M3	8
M4	8
M5	8
M6	10


Contact resistance DIN 53 482: >10^{12} Ohm / cm Dielectric strength DIN 54 481: 40 kV / mm Tolerance for lenght dimensions: +/- 0,1 mm

Order No.	SW (hexagonal)	Thread	Standard lengths in mm-increments
282 x (length)	SW 5	M2,5	from 5 mm to 45 mm
285 x	SW 6	M3	from 5 mm to 60 mm
287 x	SW 8	M4	from 5 mm to 60 mm
288 x	SW 10	M5	from 8 mm to 65 mm
289 x	SW 10	M6	from 8 mm to 60 mm

SW: width across flats

Ordering example:282 x 15 = DIA / Polyamide / SW 5 / M2,5 x 15

[Polyamide, metric thread]





Spacer bolts

Type	round
Styles	internal / external
Material	Polyamide 6.6 / DMS 824
Colour	black
Standard Pack	from 100 pcs

Internal thread lengths [mm]

L (mm)	L2 (mm)
5	3,0
from 6	4,0
from 8	6,0
from 10	8,0
from 12	10,0

External thread lengths [mm]

G1=G2	L3 (mm)
M2,5	8
M3	8
M4	8
M5	8
M6	10

Contact resistance DIN 53 482: >10^{12} Ohm / cm Dielectric strength DIN 54 481: 40 kV / mm Tolerance for lenght dimensions: +/- 0,1 mm

Order No.	Diameter (mm)	Thread	Standard lengths in mm-increments
285 rd x (length)	6	M3	from 5 mm to 60 mm
287 rd x	8	M4	from 5 mm to 60 mm

SW: width across flats

Ordering example:285 rd x 30 = DIA / rd6 / Polyamide / M3 / x 30